


Septic Tank Absorption Fields—Cherokee County, South Carolina

81° 26' 39" W

81° 24' 59" W

35° 8' 15" N

35° 8' 15" N




35° 7' 21" N

35° 7' 21" N


81° 26' 39" W

81° 24' 59" W



MAP LEGEND

Area of Interest (AOI)



Area of Interest (AOI)

Background



Aerial Photography

Soils

Soil Rating Polygons



Very limited



Somewhat limited



Not limited



Not rated or not available

Soil Rating Lines



Very limited



Somewhat limited



Not limited



Not rated or not available

Soil Rating Points



Very limited



Somewhat limited



Not limited



Not rated or not available

Water Features



Streams and Canals

Transportation



Rails



Interstate Highways



US Routes



Major Roads



Local Roads

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:20,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Cherokee County, South Carolina

Survey Area Data: Version 20, Sep 7, 2022

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Apr 22, 2022—May 10, 2022

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Septic Tank Absorption Fields

Map unit symbol	Map unit name	Rating	Component name (percent)	Rating reasons (numeric values)	Acres in AOI	Percent of AOI
Cr	Congaree silt loam	Very limited	Congaree (100%)	Flooding (1.00)	2.5	1.2%
				Depth to saturated zone (1.00)		
				Slow water movement (0.50)		
GfF	Gullied land, friable materials, 10 to 35 percent slopes	Very limited	Udorthents (100%)	Slope (1.00)	1.2	0.6%
				Slow water movement (0.50)		
MeE	Manteo channery silt loam, 15 to 35 percent slopes	Very limited	Manteo (100%)	Depth to bedrock (1.00)	67.2	32.1%
				Slope (1.00)		
				Seepage, bottom layer (1.00)		
Mv	Riverview loam, 0 to 2 percent slopes, frequently flooded	Very limited	Riverview, frequently flooded (85%)	Flooding (1.00)	5.0	2.4%
				Slow water movement (0.50)		
				Toccoa, frequently flooded (10%)		
			Toccoa, frequently flooded (10%)	Seepage, bottom layer (1.00)		
				Chewacla, frequently flooded (5%)		
			Chewacla, frequently flooded (5%)	Flooding (1.00)		
				Depth to saturated zone (1.00)		
				Seepage, bottom layer (1.00)		
				Slow water movement (0.50)		
PaE3	Pacolet clay loam, 15 to 25 percent slopes, severely eroded	Very limited	Pacolet, severely eroded (90%)	Slope (1.00)	0.2	0.1%
				Slow water movement (0.98)		
			Bethlehem (7%)	Slope (1.00)		
				Depth to bedrock (1.00)		

Map unit symbol	Map unit name	Rating	Component name (percent)	Rating reasons (numeric values)	Acres in AOI	Percent of AOI
				Slow water movement (0.50)		
			Mecklenburg, severely eroded (2%)	Slow water movement (1.00)		
				Slope (1.00)		
			Winnsboro, moderately eroded (1%)	Slow water movement (1.00)		
				Slope (1.00)		
				Depth to bedrock (0.68)		
TaC3	Tatum silty clay loam, 6 to 10 percent slopes, severely eroded	Somewhat limited	Tatum, severely eroded (100%)	Depth to bedrock (0.68)	11.1	5.3%
				Slow water movement (0.50)		
TaD3	Tatum silty clay loam, 10 to 15 percent slopes, severely eroded	Somewhat limited	Tatum, severely eroded (100%)	Slope (0.84)	25.2	12.0%
				Depth to bedrock (0.68)		
				Slow water movement (0.50)		
TaF3	Tatum silty clay loam, 15 to 35 percent slopes, severely eroded	Very limited	Tatum, severely eroded (100%)	Slope (1.00)	25.9	12.4%
				Depth to bedrock (0.68)		
				Slow water movement (0.50)		
TmC2	Tatum very fine sandy loam, 6 to 10 percent slopes, eroded	Somewhat limited	Tatum (100%)	Depth to bedrock (0.68)	1.9	0.9%
				Slow water movement (0.50)		
TmD2	Tatum very fine sandy loam, 10 to 15 percent slopes, eroded	Somewhat limited	Tatum (100%)	Slope (0.84)	34.3	16.4%
				Depth to bedrock (0.68)		
				Slow water movement (0.50)		
TmE	Tatum very fine sandy loam, 15 to 25 percent slopes	Very limited	Tatum (100%)	Slope (1.00)	4.4	2.1%
				Depth to bedrock (0.68)		
				Slow water movement (0.50)		

Map unit symbol	Map unit name	Rating	Component name (percent)	Rating reasons (numeric values)	Acres in AOI	Percent of AOI
TmE2	Tatum very fine sandy loam, 15 to 25 percent slopes, eroded	Very limited	Tatum (100%)	Slope (1.00)	30.2	14.4%
				Depth to bedrock (0.68)		
				Slow water movement (0.50)		
Totals for Area of Interest					209.3	100.0%

Rating	Acres in AOI	Percent of AOI
Very limited	136.8	65.3%
Somewhat limited	72.5	34.7%
Totals for Area of Interest	209.3	100.0%

Description

Septic tank absorption fields are areas in which effluent from a septic tank is distributed into the soil through subsurface tiles or perforated pipe. Only that part of the soil between depths of 24 and 60 inches is evaluated. The ratings are based on the soil properties that affect absorption of the effluent, construction and maintenance of the system, and public health. Saturated hydraulic conductivity (Ksat), depth to a water table, ponding, depth to bedrock or a cemented pan, and flooding affect absorption of the effluent. Stones and boulders, ice, and bedrock or a cemented pan interfere with installation. Subsidence interferes with installation and maintenance. Excessive slope may cause lateral seepage and surfacing of the effluent in downslope areas.

Some soils are underlain by loose sand and gravel or fractured bedrock at a depth of less than 4 feet below the distribution lines. In these soils the absorption field may not adequately filter the effluent, particularly when the system is new. As a result, the ground water may become contaminated.

The ratings are both verbal and numerical. Rating class terms indicate the extent to which the soils are limited by all of the soil features that affect the specified use. "Not limited" indicates that the soil has features that are very favorable for the specified use. Good performance and very low maintenance can be expected. "Somewhat limited" indicates that the soil has features that are moderately favorable for the specified use. The limitations can be overcome or minimized by special planning, design, or installation. Fair performance and moderate maintenance can be expected. "Very limited" indicates that the soil has one or more features that are unfavorable for the specified use. The limitations generally cannot be overcome without major soil reclamation, special design, or expensive installation procedures. Poor performance and high maintenance can be expected.

Numerical ratings indicate the severity of individual limitations. The ratings are shown as decimal fractions ranging from 0.01 to 1.00. They indicate gradations between the point at which a soil feature has the greatest negative impact on the use (1.00) and the point at which the soil feature is not a limitation (0.00).

The map unit components listed for each map unit in the accompanying Summary by Map Unit table in Web Soil Survey or the Aggregation Report in Soil Data Viewer are determined by the aggregation method chosen. An aggregated rating class is shown for each map unit. The components listed for each map unit are only those that have the same rating class as listed for the map unit. The percent composition of each component in a particular map unit is presented to help the user better understand the percentage of each map unit that has the rating presented.

Other components with different ratings may be present in each map unit. The ratings for all components, regardless of the map unit aggregated rating, can be viewed by generating the equivalent report from the Soil Reports tab in Web Soil Survey or from the Soil Data Mart site. Onsite investigation may be needed to validate these interpretations and to confirm the identity of the soil on a given site.

Rating Options

Aggregation Method: Dominant Condition

Component Percent Cutoff: None Specified

Tie-break Rule: Higher